

## Bentoform Plus™

**Application**

Bentoform Plus is a high quality activated calcium bentonite ideally suited for use with high pressure automated moulding lines producing grey and ductile iron castings

### TYPICAL ANALYSIS

<b>Features</b>	<ul style="list-style-type: none"> <li>High thermal durability</li> <li>High compression and tensile strengths</li> <li>Fast bond development</li> </ul>	
<b>Benefits</b>	<ul style="list-style-type: none"> <li>Reduced casting defects</li> <li>Lower bentonite consumption</li> <li>Operational cost savings</li> </ul>	
<b>General Data</b>	<b>Performance Characteristics</b>	
	CEC (Meq/100g)	86
	CEC Calcined (Meq/100g)	74
	Soluble Ca & Mg (Meq/100g)	20
	Free swell (2g/100ml)	25
<b>Moulding Properties</b>	<b>Tests in accordance with VDG P 60</b>	
	GCS (N/cm <sup>2</sup> )	11.5
	Wet Tensile Strength (N/cm <sup>2</sup> )	0.37
	DCS (N/cm <sup>2</sup> )	24.4
<b>Thermal Durability</b>	Crystalline moisture retained 650°C (%)	54
	Average property retention 650°C (%)	76
<b>Chemical Analysis</b>	SiO <sub>2</sub> 64.4 %	Na <sub>2</sub> O 0.2 %
	Al <sub>2</sub> O <sub>3</sub> 11.5 %	K <sub>2</sub> O 0.8%
	Fe <sub>2</sub> O <sub>3</sub> 0.7 %	CaO 2.8%
	MgO 2.8%	

The information and data contained herein are believed to be accurate and reliable. AMCOL Specialty Minerals makes no warranty of any kind and accepts no responsibility for the results obtained through application of this information.